

IBC1000_AFR

1000L flammable rated IBC



- Available in clear or UV blocking white - subject to availability
- Rectangular blow moulded tank of high density polyethylene, with 150mm fill lid opening in the middle of the top section. Discharge opening at the bottom of the front side
- Filling opening - DN150 with external thread, closed with screw cap, G2-plug, sealing-cap and gasket
- Rectangular grid box made of tubular steel material, with bottom plate, connected on top with tie-bar (assembled with brackets), label plate
- Antistatic outer layer - protects the container from hazardous electrostatic charge
- The earthed outlet valve discharges the electrostatic charge of the filling product
- Galvanized steel frame and pallet with 4 way forklift entry
- Operating temperatures for short period is between -65°C – 100°C and continuous is -50°C – 80°C.
- Supplied clean and pressure tested from our fully licensed IBC facility
- Easy to stack for transport or storage, load up to four high when full
- Fast to fill, easy to decant
- Easy replacement of components
- Space saving – 1 IBC replaces 4 drums, but holds the equivalent of 5
- Lightweight, safe and reliable
- Bulk orders available

ITEM	DESCRIPTION	DIMENSIONS
IBC1000_AFR	1000 litre reconditioned flammable rated IBC with steel or plastic pallet and static discharge cable. Subject to availability.	1200 x 1000 x 1160 x 60 kilos