



Our 1000L Reconditioned Flammable Rated IBCs are cleaned directly in our fully licensed IBC facility, are leak tested and ready for use. The IBCs have an antistatic outer layer which protects the container from hazardous electrostatic charge and an earthed outlet valve.

**Specifications:**

- Dimensions: 1200 L x 1000 W x 1160 H
- Weight: 60 Kgs



**Product Features:**

- Rectangular blow moulded tank of high density polyethylene, with 150mm fill lid opening in the middle of the top section. Discharge opening at the bottom of the front side
- Filling opening - DN150 with external thread, closed with screw cap, G2-plug, sealing-cap and gasket
- Rectangular grid box made of tubular steel material, with bottom plate, connected on top with tie-bar (assembled with brackets), label plate
- Antistatic outer layer - protects the container from hazardous electrostatic charge
- The earthed outlet valve discharges the electrostatic charge of the filling product
- Galvanized steel frame and pallet with 4 way forklift entry
- Operating temperatures for short period is between -65°C – 100°C and continuous is -50°C – 80°C.
- Supplied clean and pressure tested from our fully licensed IBC facility
- Easy to stack for transport or storage, load up to four high when full
- Fast to fill, easy to decant
- Easy replacement of components
- Space saving – 1 IBC replaces 4 drums, but holds the equivalent of 5
- Lightweight, safe and reliable

**BULK ORDERS AVAILABLE**